



Cold water softeners for warewashing & laundry

The Autosoft range of cold water softeners provide softened water for warewashing and laundry giving better washing results and protecting equipment from harmful scale and other minerals.

Timer or metered control. **TIMER CONTROL VALVE** - Ion-Exchange Resin is flushed with brine solution to re-charge at a set time. Ideal for busy sites with fixed operating times. **METERED CONTROL VALVE** - Ion-Exchange Resin is flushed with brine solution to re-charge after a pre-determined measured volume of water is used. Perfect for saving money on low-usage equipment or irregular operating times.



Cold water softeners installation requirements

WATER PRESSURE	MINIMUM 1.5 BAR* MAXIMUM 6.0**
WATER CONNECTION	¾" BSP INLET AND OUTLET. ADEQUATE DRAINAGE AND OVERFLOW FACILITIES REQUIRED
WATER TEMPERATURE	MAXIMUM 35°C. PROTECT FROM FREEZING
ELECTRICAL SUPPLY	24/240V VAC 3 AMPS – MUST BE ON A MAINTAINED SUPPLY, I.E. NEVER SWITCH OFF

*NOTE IF PRESSURE IS LESS THAN 1.5 BAR EUROPEAN WATERCARE RECOMMENDS THE INSTALLATION OF A PUMPED SOFTENER.

**NOTE IF PRESSURE EXCEEDS 3 BAR A PRESSURE REDUCING VALVE MUST BE FITTED TO KEEP WARRANTY VALID

Models and Specs overleaf



**AUTOMATIC COLD
WATER SOFTENERS**

Metered Cold Water Softeners	Dimensions (mm)			Capacity (Ltrs)	Part No
	Height	Width	Depth		
COLD WATER SOFTENER - 10 LITRE	680	280	450	1494	E10M
COLD WATER SOFTENER - 14 LITRE	720	280	450	2278	E14M
COLD WATER SOFTENER - 18 LITRE	735	280	450	2929	E18M
COLD WATER SOFTENER - 23 LITRE	800	280	450	3743	E23M
COLD WATER SOFTENER - 30 LITRE	1127	316	559	4882	E30M

Logix Digital Metered Cold Water Softeners	Dimensions (mm)			Capacity (Ltrs)	Part No
	Height	Width	Depth		
COLD WATER SOFTENER - 10 LITRE	625	280	450	1494	AT10M
COLD WATER SOFTENER - 14 LITRE	665	280	450	2278	AT14M
COLD WATER SOFTENER - 18 LITRE	665	280	450	2929	AT18M
COLD WATER SOFTENER - 23 LITRE	780	280	450	3743	AT23M
COLD WATER SOFTENER - 30 LITRE	1127	316	559	4882	AT30M

Timer Controlled Cold Water Softeners	Dimensions (mm)			Capacity (Ltrs)	Part No
	Height	Width	Depth		
MINI WATER SOFTENER - 5 LITRE	580	205	390	664	E5T - MICRO
MINI WATER SOFTENER - 5 LITRE	580	280	450	664	E5T
WATER SOFTENER - 10 LITRE	680	280	450	1494	E10T
WATER SOFTENER - 14 LITRE	720	280	450	2278	E14T
WATER SOFTENER - 18 LITRE	735	280	450	2929	E18T
WATER SOFTENER - 23 LITRE	800	280	450	3743	E23T
WATER SOFTENER - 30 LITRE	1127	316	559	4882	E30T

Logix Digital Timer Controlled Cold Water Softeners	Dimensions (mm)			Capacity (Ltrs)	Part No
	Height	Width	Depth		
MINI WATER SOFTENER - 5 LITRE	525	205	390	664	AT5 - MICRO
MINI WATER SOFTENER - 5 LITRE	525	280	450	664	AT5
WATER SOFTENER - 10 LITRE	625	280	250	1494	AT10
WATER SOFTENER - 14 LITRE	665	280	450	2278	AT14
WATER SOFTENER - 18 LITRE	665	280	450	2929	AT18
WATER SOFTENER - 23 LITRE	780	280	450	3743	AT23
WATER SOFTENER - 30 LITRE	1127	316	559	4882	AT30



01279 780 250 | info@watercare.co.uk

European WaterCare Ltd | Regal House | South Road | Harlow | CM20 2BL.

[@europeanwtcare](https://twitter.com/europeanwtcare) | www.watercare.co.uk