



Hot water softeners for warewashing & laundry

The Autosoft range of hot water softeners provide softened water for warewashing and laundry giving better washing results and protecting equipment from harmful scale and other minerals.

Timer or metered control. **TIMER CONTROL VALVE** - Ion-Exchange Resin is flushed with brine solution to re-charge at a set time. Ideal for busy sites with fixed operating times. **METERED CONTROL VALVE** - Ion-Exchange Resin is flushed with brine solution to re-charge after a pre-determined measured volume of water is used. Perfect for saving money on low-usage equipment or irregular operating times.



Cold water softeners installation requirements

WATER PRESSURE	MINIMUM 1.5 BAR* MAXIMUM 6.0**
WATER CONNECTION	¾ TO 1" DEPENDANT ON UNIT SIZE. ADEQUATE DRAINAGE AND OVERFLOW FACILITIES REQUIRED
WATER TEMPERATURE	MAXIMUM 60°C. PROTECT FROM FREEZING
ELECTRICAL SUPPLY	24/240V VAC 3 AMPS – MUST BE ON A MAINTAINED SUPPLY, I.E. NEVER SWITCH OFF

*NOTE IF PRESSURE IS LESS THAN 1.5 BAR EUROPEAN WATERCARE RECOMMENDS THE INSTALLATION OF A PUMPED SOFTENER.

**NOTE IF PRESSURE EXCEEDS 3 BAR A PRESSURE REDUCING VALVE MUST BE FITTED TO KEEP WARRANTY VALID

Models and Specs overleaf




**AUTOMATIC HOT
WATER SOFTENERS**

Description	Dimensions (mm)			Capacity (Ltrs)	Part No
	Height	Width	Depth		
HOT WATER SOFTENER - 5 LITRE	580	205	390	664	HW5
HOT WATER SOFTENER - 10 LITRE	680	280	450	1494	HW10
HOT WATER SOFTENER - 14 LITRE	680	280	450	2278	HW14
HOT WATER SOFTENER - 18 LITRE	780	280	450	2929	HW18
HOT WATER SOFTENER - 23 LITRE	800	280	450	3743	HW23
HOT WATER SOFTENER - 30 LITRE	1135	361	559	4882	HW30



01279 780 250 | info@watercare.co.uk

European WaterCare Ltd | Regal House | South Road | Harlow | CM20 2BL.

 [@europeanwtcare](https://twitter.com/europeanwtcare) | www.watercare.co.uk