



## Commercial Softeners Approximate Sizes

Enquire  
for project  
advice and  
specifications



### Autosoft Cold Water Softeners - Installation Specifications

Softener connection information.

Water pressure	Water connection	Water temperature	Electrical supply
Minimum 1.5 bar* Maximum 5.0 bar**	¾" Bsp inlet and outlet. Adequate drainage and overflow facilities required	Maximum 35°C Protect from freezing	24/240v vac 3 amps – must be on a maintained supply, i.e. never switch off

### Autosoft Hot Water Softeners - Installation Specifications

Automatic hot feed up to 50 degrees centigrade - For dishwasher or glasswasher, EWC valve, mounted in moulded cabinet.

Water pressure	Water connection	Water temperature	Electrical supply
Minimum 1.5 bar* Minimum 5.0 bar **	¾ To 1" dependent on unit size. Adequate drainage and overflow facilities required	Maximum 50°C Protect from freezing	24/240v vac 3 amps – must be on a maintained supply, do not switch off

\* Note if pressure is less than 1.5 bar watercare recommends the installation of a pumped softener

\*\* Note if pressure exceeds 5 bar a pressure reducing valve must be fitted to keep warranty valid

### Commercial Cold Water Softeners Simplex Configuration Sizes

Model	10	14	18	20	23	30	40	50	60	70	80	120	180	250
A (mm) - cylinder	652	779	845	982	820	1109	1338	1592	1440	1592	1592	1831	1795	2024
B (mm) - cylinder	204	204	238	204	254	254	254	254	305	331	331	356	534	610
C (mm) - brine tank	584	584	628	628	800	800	800	870	870	1060	1060	1060	1080	1080
D (mm) - brine tank	324	324	444	444	465	465	465	560	560	560	560	560	755	755
Salt (kg) per regeneration	1.5	2.4	2.8	3	3.5	4.2	5.6	7	8	9.5	10.5	16	23.5	32

Description	Part No
25KG TABLET SALT	SALT-TAB-25KG

**These units are made to order, speak to a representative for more information. Call 01279 780250**  
Please refer to information pages for capacities.

