



PROFESSIONAL WATER SOFTENING

hot water softener

Services

Water pressure minimum 1.5 bar*, maximum 5 bar**

Water connection 3/4" bsp inlet and outlet. Adequate drainage and overflow facilities required.

Water temperature maximum 50°C.***

Protect from freezing

Electrical supply 240v uk power socket – must be on a maintained supply, i.e., never switch off.

*please note, if pressure is less than 1.5 bar, watercare recommends the installation of a pumped water softener. speak to a sales representative for more information.

**please note, if the pressure exceeds 3 bar, watercare

recommends

the installation of a pressure reducing valve. water pressure over 5 bar will void your water softener warranty.

***please note, if the temperature exceeds 50°C, watercare recommends the installation of a thermostatic mixing valve to keep warranty valid.

Installation & set-up guide,
warranties and helpful hints



watercare.co.uk




HS-10 / HS-16HX / HS-23 / HS-30





PROFESSIONAL WATER SOFTENING



Model	H	W	D	Capacity ltrs	Code
10 ltr Metered Cold Softener	580	280	450	1667	HS-10
16 ltr Metered Cold Softener	580	280	450	2667	HS-16X
23 ltr Metered Cold Softener	735	280	450	3667	HS-23
30 ltr Metered Cold Softener	1200	316	559	5000	HS-30

Capacity based on water hardness of 21° Clarke / 300 PPM

for warewashing & laundry

The AutoSoft range of hot water softeners provide softened water for warewashing and laundry giving better washing results and protecting equipment from harmful scale and other minerals.

Metered control valve

Ion-Exchange Resin is flushed with brine solution to recharge after a pre-determined measured volume of water is used.

Not only do our range of cold water softeners boast unrivalled performance, their water saving technology means they only regenerate when necessary. By using considerably less water and salt, our softeners help reduce environmental impact plus save you money!

Enjoy prolonged equipment life, more efficient washing, and professional results every time.

Digital Display

Now with a fully electronic control system, our cold water softeners now have a fully digital display, fitted for extra benefits. This makes them easier to service, quicker to set-up and have increased regeneration efficiency.

Applications

Hot water fed glasswashers, dishwashers and laundry washing machines.

Features & Benefits

- Wide range of capacities to suit every application
- Metered control valve – only regenerates when necessary
- Electronic control system, the back-lit display is easy to see in dark areas.
- Automatic service reminder at 52 weeks
- Easy set up and installation
- Made in Britain
- Suitable for hot water fed warewashing equipment
- Available in sizes 10, 16, 23 and 30
- Proportional Brining
- Counter-flow regeneration for improved regen efficiency



Accessories

25kg tablet salt

Thermostatic mixing valve 3/4" fittings

Cold and hot water softener service kit (cages and seals)

S10 transformer (power pack)

Code

SALT-TAB-25KG

WATT6210C346210C

S10-SEALSANDSPACER-ASSY

EWC-S10-TRANSFORMER



WaterCare | Regal House | South Road | Harlow | Essex | CM20 2BL
Tel: 01279 780250 | Email: info@watercare.co.uk | Visit: www.watercare.co.uk

HS-10 / HS-16HX / HS-23 / HS-30

