

high-volume commercial hot water softener

Features

Flexible modular hot water feed water softening system for large volumes of treated water.


Applications

Hot water feed softening applications, ideal for commercial kitchens, hotels and hospitality.

Commercial Hot Water Softeners Simplex Configuration Sizes

Model	CS30	CS50	CS80
A (mm) - cylinder	1110	1592	1592
B (mm) - cylinder	254	254	331
C (mm) - brine tank	850	775	975
D (mm) - brine tank	550	680	685
Salt (kg) per regeneration	4.2	7	10.5

These units are made to order.
Speak to a representative for more information. Call 01279 780250.



Hot Water Commercial Water Softener Installation Requirements

Water Pressure	Water Connection	Water Temperature	Electrical Supply
Minimum 1.5 bar* Maximum 5.0 bar**	¾" To 2" dependent on unit size. Adequate drainage and overflow facilities required	Maximum 50°C Protect from freezing	24/240v vac 3 amps – must be on a maintained supply, i.e. never switch off

* Note if pressure is less than 1.5 bar watercare recommends the installation of a pumped softener

** Note if pressure exceeds 5 bar a pressure reducing valve must be fitted to keep warranty valid

Description	Part No
25KG TABLET SALT	SALT-TAB-25KG



watercare.co.uk